

Product Information

Will include the below Information

Glaze Specifications

Item	Properties
Glaze Type	Transparent, white oxides and glazes
Application	Manual spray application (Hand Applied)
Surface Finish	Glossy
Glaze Variation	Variable ± 3 grades
Firing temperature	1000-1060 °C

Important Notes

- 1. Color Variations:** Due to the traditional kiln firing process, some natural color variation is to be expected, including subtle differences in shade or the presence of occasional dots on the surface of the tiles.
- 2. Dimensional Variations:** Tiles are either hand-pressed or pre-cut to size, which may result in slight dimensional variations of $\pm 1-2$ mm.

Installation Guide

- 1. Professional Installation:** Installation should be carried out by an experienced tiler who is familiar with the specific requirements of these tiles.
- 2. Grout Joint Spacing:** A minimum grout joint of 2mm is recommended between tiles to accommodate any dimensional variations.
- 3. Shade Distribution:** Prior to installation, inspect the tiles and ensure that different shades are evenly distributed across the surface, avoiding the clustering of similar tones in one area.
- 4. Alignment:** Utilize a laser level and plastic spacers to ensure precise alignment of grout joints, both vertically and horizontally.
- 5. Adhesive Application:** Tiles should be adhered using a suitable adhesive for application on plaster walls or screed floors.